



## Metachain HTS

High performance, synthetic chain lubricant



### Description

Metachain HTS is a high performance, fully synthetic lubricant specifically designed to lubricate and protect the chain systems of a variety of industrial ovens. It is formulated from a blend of synthetic base fluids carefully selected to deliver excellent lubrication properties at high operating temperatures. The advanced additive system minimizes friction and wear and protects against thermo-oxidative degradation ensuring that chains are kept free from carbon deposit build-up.

Metachain HTS is suitable for use at operating temperatures up to 280°C.

### Features and benefits

- Excellent resistance to thermo-oxidative degradation minimizes carbon deposit build-up
- Fully synthetic base fluids and anti-wear additives deliver outstanding lubrication at high operating temperatures
- Suitable for use on most types ovens chain systems
- Capable of operating at temperatures up to 280°C

### Recommended instructions for use

Metachain HTS should be used as supplied. Lubrication systems should ideally be drained and flushed prior to introduction of HTS. For optimal results chains and tracks should be cleaned during change-over.

Global specialists in high-performance lubricants

**Metalube Limited**, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester M44 5EG, UK  
Tel: +44 (0)161 775 7771 Fax: +44 (0)161 775 7511 post@metalube.co.uk www.metalube.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927000



Cert No 2367QM8001



## Metachain HTS

### Pack sizes

20 ltr and 205 drums

### Technical data (typical values)

Property	Test method	Result
Appearance	MSTM 1	Clear/yellow fluid
Base fluid type	-	Synthetic ester
Kinematic viscosity at 40°C	MSTM 27	220 cSt
Density at 20°C	MSTM 23	0.97
Operating Temperature		-30°C to +280°C

### Storage

Store out of direct sunlight. Storage temperature should be controlled to between 5°C and 35°C.

The product information in this publication is based on knowledge and experience at the time of printing. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue date 09-13

Global specialists in high-performance lubricants

**Metalube Limited**, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester M44 5EG, UK  
Tel: +44 (0)161 775 7771 Fax: +44 (0)161 775 7511 post@metalube.co.uk www.metalube.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927000



Cert No 2367QM8001