



OCG™ 1000M

Protective grease for overhead line conductors



Description

OCG1000M is a high performance grease specifically developed for the protection of aluminium, aluminium alloy and steel reinforced overhead conductors, earthwires and their associated fittings. The unique combination of additives and base fluids delivers outstanding corrosion protection combined with long term thermal stability resulting in excellent protection throughout the service life of the conductor.

OCG1000M utilises a non-melting thickener system that results in a grease with a drop point over 300°C and extremely low oil separation at operating temperatures up to 150°C. This minimises oil migration from the core to the outer surface of the conductor helping to reduce corona effects.

Features and benefits

- Excellent thermal stability maximises product integrity over the operational life of the conductor
- Extremely low oil separation
- Maintains flexibility down to -20°C, prevents cracking and flaking of the grease film at low ambient temperatures
- Provides good corrosion protection to steel, galvanised steel, aluminium and aluminium alloy conductor components
- Reduces abrasive wear and fretting on the conductor that can result due to thermal expansion/contraction and varying weather conditions

Global specialists in high-performance lubricants

Metalube Limited, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester M44 5EG, UK
Tel: +44 (0)161 775 7771 Fax: +44 (0)161 775 7511 post@metalube.co.uk www.metalube.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927000



Cert No 2367QM8001



OCG™ 1000M

Approvals and standards

OCG1000M meets the requirements of:

- IEC 61394:2011 with the designation 20A150

Recommended instructions for use

OCG1000M is designed for application at ambient temperatures and does not require heating prior to use.

Note: Greases of different types may not be compatible with OCG1000M - application equipment should be thoroughly cleaned to remove residues of previous lubricants to avoid incompatibility issues.

Pack sizes

OCG1000M is available in 180 kg drums

Technical data (typical values)

Property	Test method	Result
Appearance	MSTM 1	Brown tenacious grease
Typical S.G. @ 20°C		0.93
Base oil type	–	Mineral oil
Worked penetration	IP50	284 mm/10
Drop point	IP132	>300°C
Oil separation (1 hour at 150°C)	IP121 (modified)	0.01%

Storage

Store OCG1000M out of direct sunlight and protect from frost. Storage temperature should ideally be controlled to between 5°C and 35°C.

The product information in this publication is based on knowledge and experience at the time of printing. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue date 11-15

Global specialists in high-performance lubricants

Metalube Limited, 4 Huntsman Drive, Northbank Industrial Park, Irlam, Manchester M44 5EG, UK
Tel: +44 (0)161 775 7771 Fax: +44 (0)161 775 7511 post@metalube.co.uk www.metalube.co.uk

Company registration number: 2263118; Company registered in England VAT registration number GB108244927000



Cert No 2367QM8001